



Fibre optic cable

LTMC-S

Article number: 77394

14-01-2022

Description

192x SM G.657.A1 (8x24)

The Loose Tube Mini Cable 'Slim' (LTMC-S) is a non-metallic, longitudinal water-protected fibre optic cable, with a smallest possible outer diameter and optimized fibre density, suitable for Access or FTTx applications. Installation: blowing into mini ducts.



* This image may differ from the actual product.

Trading information

Product group	Fibre optic cable
Type	LTMC-S
Net. Weight	54 kg/km
Sheath marking	ACE - TKF LTMC-S 192x SM G.657.A1 (8x24) A-DQ(ZN)2Y 77394 {Batch} {Year} {Length}

Trade lengths

Minimal order

(77394 / 8713182397128)	1 MTR
-------------------------	-------



Fibre optic cable

LTMC-S

Article number: 77394

14-01-2022

Construction characteristics

Cable type	LTMC
Cable metal free	Yes
With strain relief	Yes
Type of strain relief	FRP
Longitudinal water blocking cable	Yes
Longitudinal water blocking	Yes
Number of layers	1 Layer
Colour outer sheath	Black
Outer diameter approx.	7.6 mm
Outer sheath thickness	0.45 mm
Material outer sheath	HDPE
Number of fibres	192
Number of cores	8
Number of fibres per tube	24

Properties

Application	Outside
Blow in	Yes
Type of tube	Loose tube, gel filled
Operational temperature range Ta1 - Tb1	-40 / 70 °C
Max. attenuation increase during Ta1 - Tb1	0.05 dB
TC sample length for TC acc F1 or F12	1,000 m
Installation temperature	-15 / 55 °C
Transportation and storage temperature	-45 / 70 °C



Fibre optic cable

LTMC-S

Article number: 77394

14-01-2022

Technical characteristics

Standardization	EN IEC 60794-5-10
Test procedures	IEC 60794-1-2
Longitudinal watertight construction	Super Absorbing Polymer

Mechanical characteristics

Tensile load short term (Tm)	4,000 N
Max. fiber strain at Tm	0.4 %
Tensile load long term (Tl)	1,000 N
Max. fibre elongation at Tl	0 %
Min. bending radius during installation	155 mm
Min. permitted bending radius, stationary application/permanent installation	115 mm

Optical characteristics

Fibre type	Single mode 9/125
Optical fibre standard	ITU-T G.657.A1
Max. attenuation @ 1310 nm	0.35 dB/km
Max. attenuation @ 1550 nm	0.22 dB/km
Max. attenuation @ 1625 nm	0.25 dB/km

Other characteristics/features

Halogen free according to EN 60754-1/2	Yes
Reaction-to-fire according to EN 13501-6: Class	Fca
UV resistant	Yes