

All rights reserved



## 1. General

#### 1.1 Scope

This Specification covers the design requirements and performance standard for the supply of optical fibre cable in the industry. YOFC ensures a stable quality control system for our cable products through several programs including ISO 9001, ISO 14001 and OHS.

Cable type	Application
GJYFXHP-4,12B6a1	Universal cable

#### 1.2 Reference

The cable offered by YOFC are designed, manufactured and tested according to the standards as follows:

ITU-T G.657	Characteristics of a bending-loss insensitive single-mode optical fibre and cable for the access network
IEC 60794-1-1	Optical fibre cables-part 1-1: Generic specification-General
IEC 60794-1-21	Optical fiber cables- part1-21-Generic specification-Basic optical cable test procedure-Mechanical test methods
IEC 60794-1-22	Optical fiber cables- part1-22-Generic specification-Basic optical cable test procedure-Environmental test methods
IEC 60794-3	Optical fibre cables – Part 3 Outdoor cables – Sectional specification
IEC 60794-3-10	Optical fibre cables - Part 3-10 Outdoor cables - Family specification for duct, directly buried and lashed aerial optical telecommunication cables

#### 1.3 Life Time

Optical fibre cables supplied in compliance with this specifications is capable to withstand the typical service condition for a period of 25 years without detriment to the operation characteristics of the cable.

## 1.4 Application

Item	Value	
Installation temperature	-10°C∼+50°C	
Operation temperature	-30°C∼+70°C	
Storage temperature	-40°C ∼+70°C	
Bending radius(Installation)	20D(D: Cable diameter)	
Bending radius(Operation)	10D(D: Cable diameter)	



# 2. Optical Fibre

Optical properties of the SM fiber are achieved through a germanium doped silica based core with a pure silica cladding which meets ITU-T G657A1, UV curable acrylate protective coating is applied over the glass cladding to provide the necessary maximum fiber lifetime.

Geometrical, optical, and mechanical characteristics of fiber in cable as the following table:

Category	Description	Specification		
	Cladding diameter	$125.0 \pm 0.7 \mu m$		
	Cladding non-circularity	≤0.7 %		
Geometric characteristic	Core-cladding concentricity error	≤ 0.5µm		
Geometric characteristic	Coating diameter (uncolored)	245±10μm		
	Coating diameter (colored)	250±15μm		
	Coating-cladding concentricity error	≤ 12µm		
	Attenuation coefficient at 1310 nm	≤0.38dB/km		
	Attenuation coefficient at 1550 nm	≤0.25dB/km		
	Attenuation coefficient at 1625 nm	≤0.30dB/km		
	Mode filed diameter at 1310nm	8.4~9.2μm		
	Cable cutoff wavelength (λcc)	≤ 1260 nm		
Transmission characteristic	Zero Dispersion Wavelength (λ0)	$1300 \le \lambda 0 \le 1324 \text{ nm}$		
	Zero Dispersion Slope (S0)	≤0.092 ps/(nm2.km)		
	Dispersion coefficient at (1285nm-1330nm)	≤ 3.5ps/(nm.km)		
	Dispersion coefficient at 1550 nm	≤ 18ps/(nm.km)		
	Macro-bend loss (10 turns, 15mm,radius)	≤0.25 dB at 1550nm ≤ 1.0 dB at 1625nm		
	Macro-bend loss (1 turn, 10mm radius)	≤0.75 dB at 1550nm ≤ 1.5 dB at 1625nm		
	Proof stress level	≥ 100kpsi (0.69Gpa)		
Mechanical characteristic	Fibre curl radius	≥4 m		
Other Characteristics	Conform to IEC 60793-2-50			




# 3. Optical Cable

#### 3.1 Technical Characteristics

- Several optical fibres are housed in a soft tube.
- Aramid yarns are used in the cable core as the strength member.
- LSZH with two FRPs is applied over the cable core as outer sheath.

#### 3.2 Cross Section of Cable



(Schematic for reference only,

#### 3.3 Fibre Identification

The color code of fibres will be identification in accordance with the following color sequence, other sequence also is available.

Fibre color	1	2	3	4	5	6	7	8	9	10	11	12
code	White	Red	Yellow	Green	Blue	Grey	Brown	Black	Violet	Turquoise	Orange	Pink

## 3.4 Cable structure and relevant properties

## 3.4.1 Dimensions and Descriptions of Cable Constructions

Item	Contents	Value		
Item	Contents	4	12	
	Fiber count	4	12	
Soft tube	Color	White		
Soft tube	Material	LSZH		
	Stripability optical element	≥1000mm, down to primary coating		
Strength member	Assemble	Aramid yarn & Two FRPs		
Material		LSZH with UV resistance		
Outer sheath	Color	White		
	Thickness(mm)	Nom. 1.7		
Cable diameter(±0.3mm)		5.5		
Cable weight(kg/kr	m) Approx.	35		



#### 3.4.2 Mechanical Performance of Cable

Tensile perf	formance(N)	Crush(N/100mm)		
Long term load	Short term load	Long term load	Short term load	
300	1000	300	500	

# 4. Mechanical, Physical and Environmental Test Characteristics

The mechanical and environmental performance of the cable are in accordance with the following table. Unless otherwise specified, all attenuation measurements required in this section shall be performed at 1550nm.

No.	Items	Test Method	Requirements
4.1	Tensile performance	IEC 60794-1-21-E1 Load: 1000N Cable length under tension: ≥50m. Duration of load sustain: 10 min.	Fibre strain $\leq 0.6\%$ $\Delta a \leq 0.05 \text{dB}$ . No damage to outer jacket.
4.2	Crush	IEC 60794-1-21-E3 Load: 500N for 10min	$\Delta a \leq 0.05 dB$ after test. No damage to outer jacket.
4.3	Impact	IEC 60794-1-21-E4 Hammer radius: 12.5mm Number of impacts: 3 Impact energy:1J.	$\Delta a \leq 0.05 dB$ after test. No damage to outer jacket.
4.4	Repeated bending	IEC 60794-1-21-E6 Bending radius: 20*D Cycles: 30 Load: 20N	$\Delta a \le 0.05 dB$ after test. No damage to outer jacket.
4.5	Torsion	IEC 60794-1-21-E7 Test length=1m Load=20N Turns=±180° Number of cycles: 10	$\Delta a \le 0.05 dB$ after test. No damage to outer jacket.
4.6	Bend	IEC 60794-1-21-E11A Radius r=10D (D: cable diameter) Turns: 4 Cycles: 3	$\Delta a \le 0.05 dB$ after test. No damage to outer jacket.
4.7	Temperature cycling	IEC 60794-1-22-F1 Temperature range: $T_{A1}$ : -30°C, $T_{A2}$ : -40°C $T_{B1}$ :+70°C, $T_{B2}$ : +70°C Cycles: 2 Dwell time: 8h	During test: $ \Delta\alpha \leq 0.05 \text{ dB/km for } T_{A1} \text{ and } T_{B1} $ $ \Delta\alpha \leq 0.15 \text{ dB/km for } T_{A2} \text{ and } T_{B2} $ After test: $ \Delta\alpha \text{ reversible } $
4.8	Water penetration	IEC 60794-1-22-F5C Time: 24 hours Sample length: 3m Water height: 1m	No water leakage.
4.9	CPR	Dca-s1 d2 a1	



# 5. Packaging and Drum

## 5.1 Cable Sheath Marking

Unless otherwise specified, the cable sheath marking shall be as follows:

Color: White Interval: 1m

Outer sheath marking legend can be changed according to user's requests.

## 5.2 Reel Length

Standard reel length: 2km/reel, other length is also available.

#### 5.3 Cable Drum

The cables are packed in wooden drums.

#### 5.4 Cable Packing

Both ends of the cable will be sealed with suitable plastic caps to prevent the entry of moisture during shipping, handling and storage.

# 6. Change history

2024.11.19	From V1.0 to V2.0	Change the cable structure		

www.maxeta.no