



All rights reserved

1. General

1.1 Scope

This Specification covers the design requirements and performance standard for the supply of optical fibre cable in the industry. YOFC ensures a stable quality control system for our cable products through several programs including ISO 9001, ISO 14001 and OHS.

Cable type	Application
GJFXHP-24B6a1	Universal cable

1.2 Reference

The cable offered by YOFC are designed, manufactured and tested according to the standards as follows:

ITU-T G.657	Characteristics of a bending-loss insensitive single-mode optical fibre and cable for the access network
IEC 60794-1-1	Optical fibre cables-part 1-1: Generic specification-General
IEC 60794-1-21	Optical fiber cables- part1-21-Generic specification-Basic optical cable test procedure-Mechanical test methods
IEC 60794-1-22	Optical fiber cables- part1-22-Generic specification-Basic optical cable test procedure-Environmental test methods
IEC 60794-2	Optical fibre cables – Part 2: Indoor cables – Sectional specification
IEC 60794-2-20	Optical fibre cables - Part 2-20 Indoor cables - Family specification for multi-fibre optical cables

1.3 Life Time

Optical fibre cables supplied in compliance with this specifications is capable to withstand the typical service condition for a period of 25 years without detriment to the operation characteristics of the cable.

1.4 Application

Item	Value	
Installation temperature	-10°C ∼+50°C	
Operation temperature	-30℃~+70℃	
Storage temperature	-40°C∼+70°C	
Bending radius(Installation)	20D(D: Cable diameter)	
Bending radius(Operation)	10D(D: Cable diameter)	

2. Optical Fibre

Optical properties of the SM fiber are achieved through a germanium doped silica based core with a pure silica cladding which meets ITU-T G657A1, UV curable acrylate protective coating is applied over the glass cladding to provide the necessary maximum fiber lifetime.

Geometrical, optical, and mechanical characteristics of fiber in cable as the following table:

Category	Description	Specification	
	Cladding diameter	$125.0 \pm 0.7 \mu m$	
Geometric characteristic	Cladding non-circularity	≤0.7 %	
	Core-cladding concentricity error	≤ 0.5µm	
Geometric characteristic	Coating diameter (uncolored)	245±10μm	
	Coating diameter (colored)	250±15μm	
	Coating-cladding concentricity error	≤ 12μm	
	Attenuation coefficient at 1310 nm	≤0.38dB/km	
	Attenuation coefficient at 1550 nm	≤0.25dB/km	
	Attenuation coefficient at 1625 nm	≤0.30dB/km	
	Mode filed diameter at 1310nm	8.4~9.2μm	
	Cable cutoff wavelength (λcc)	≤ 1260 nm	
Transmission characteristic	Zero Dispersion Wavelength (λ0)	$1300 \le \lambda 0 \le 1324 \text{ nm}$	
onarastorismo	Zero Dispersion Slope (S0)	≤0.092 ps/(nm2.km)	
	Dispersion coefficient at (1285nm-1330nm)	≤ 3.5ps/(nm.km)	
	Dispersion coefficient at 1550 nm	≤ 18ps/(nm.km)	
	Macro-bend loss (10 turns, 15mm,radius)	≤0.25 dB at 1550nm ≤ 1.0 dB at 1625nm	
	Macro-bend loss (1 turn, 10mm radius)	≤0.75 dB at 1550nm ≤ 1.5 dB at 1625nm	
Mechanical characteristic	Proof stress level	≥ 100kpsi (0.69Gpa)	
	Fibre curl radius	≥4 m	
Other Characteristics	Conform to IEC 60793-2-50		

3. Optical Cable

3.1 Technical Characteristics

- Several optical fibres are housed in a soft tube.
- Aramid yarns are used in the cable core as the strength member.
- LSZH with two FRPs is applied over the cable core as outer sheath.

3.2 Cross Section of Cable



(Schematic for reference only,

3.3 Fibre Identification

The color code of fibres will be identification in accordance with the following color sequence, other sequence also is available.

	1	2	3	4	5	6	7	8	9	10	11	12
	White	Red	Yellow	Green	Blue	Grey	Brown	Black	Violet	Turquoise	Orange	Pink
Fibre color												
code	13	14	15	16	17	18	19	20	21	22	23	24
	White	Red	Yellow	Green	Blue	Grey	Brown	Natural	Violet	Turquoise	Orange	Pink

3.4 Cable structure and relevant properties

3.4.1 Dimensions and Descriptions of Cable Constructions

Item	Contents	Value	
	Fiber count	24	
Soft tube	Color	White	
Soft tube	Material	LSZH	
	Stripability optical element	≥1000mm, down to primary coating	
Strength member	Assemble	Aramid yarn & Two FRPs	
	Material	LSZH with UV resistance	
Outer sheath	Color	Black	
	Thickness(mm)	Nom. 1.7	
Cable diameter(±0.2mm)		6.0	
Cable weight(kg/km) Approx.		43	

3.4.2 Mechanical Performance of Cable

Tensile perf	ormance(N)	Crush(N	/100mm)
Long term load	Short term load	Long term load	Short term load
300	1000	300	500

4. Mechanical, Physical and Environmental Test Characteristics

The mechanical and environmental performance of the cable are in accordance with the following table. Unless otherwise specified, all attenuation measurements required in this section shall be performed at 1550nm.

No.	Items	Test Method	Requirements
4.1	Tensile performance	IEC 60794-1-21-E1 Load: 1000N Cable length under tension: ≥50m. Duration of load sustain: 10 min.	Fibre strain≤0.6% Δa≤0.05dB. No damage to outer jacket.
4.2	Crush	IEC 60794-1-21-E3 Load: 300N for 10min and 500N for 1min	$\Delta a \le 0.10 dB$ under long term load and Δa reversible after short term load. No damage to outer jacket.
4.3	Impact	IEC 60794-1-21-E4 Hammer radius: 12.5mm Number of impacts: One in 3 different places spaced not less than 500 mm apart. Impact energy:1J.	$\Delta a \leq 0.05 dB$ after test. No damage to outer jacket.
4.4	Repeated bending	IEC 60794-1-21-E6 Bending radius: 20*D Cycles: 30 Load: 20N	$\Delta a \le 0.05 dB$ after test. No damage to outer jacket.
4.5	Torsion	IEC 60794-1-21-E7 Test length=1m Load=20N Turns=±180° Number of cycles: 10	$\Delta a \leq 0.05 dB$ after test. No damage to outer jacket.
4.6	Bend	IEC 60794-1-21-E11A Radius r=10D (D: cable diameter) Turns: 4 Cycles: 3	$\Delta a \le 0.05 dB$ after test. No damage to outer jacket.
4.7	Temperature cycling	IEC 60794-1-22-F1 Temperature range: T_{A1} : -30°C, T_{A2} : -40°C T_{B1} :+70°C, T_{B2} : +70°C Cycles: 2 Dwell time: 8h	During test: $ \Delta\alpha \leq 0.05 \text{ dB/km for } T_{A1} \text{ and } T_{B1} $ $ \Delta\alpha \leq 0.15 \text{ dB/km for } T_{A2} \text{ and } T_{B2} $ After test: $ \Delta\alpha \text{ reversible } $
4.8	Water penetration	IEC 60794-1-22-F5B Time: 24 hours Sample length: 3m Water height: 1m	No water leakage.(Not including the soft tube)
4.9	CPR	Dca-s1 d2 a1	

5. Packaging and Drum

5.1 Cable Sheath Marking

Unless otherwise specified, the cable sheath marking shall be as follows:

Color: White Interval: 1m

Outer sheath marking legend can be changed according to user's requests.

5.2 Reel Length

Standard reel length: 2km/reel, other length is also available.

5.3 Cable Drum

The cables are packed in wooden drums.

5.4 Cable Packing

Both ends of the cable will be sealed with suitable plastic caps to prevent the entry of moisture during shipping, handling and storage.

www.maxeta.no