

| UPS | |
|----------------------|--------------|
| Manufacturer | SOCOMEK |
| Model | NPE-1000-LCD |
| Performance (kVA/kW) | 1.0/0.6 |

| Nominal Voltage | |
|------------------------|--------------|
| Input (V) | 230 V (Ph+N) |
| Output (V) | 230 V (Ph+N) |

| Nominal Current | |
|------------------------|-----|
| Input (A) | 4.6 |
| Output (A) | 4.4 |

| Static Bypass | |
|---|--|
| <input type="checkbox"/> Yes | <input checked="" type="checkbox"/> No |
| If Yes, Maximum allowed I ² t (A ² s) | |

| Short circuit capability | |
|---------------------------------|------|
| Short time | |
| Current (A) | 5.19 |
| Maximum time (s) | 0.02 |
| Long time | |
| Current (A) | 5.19 |
| Maximum time (s) | 0.02 |

| Maximum thermal overload | |
|---------------------------------|-----|
| Current (A) | 4.9 |

| Installation data | |
|----------------------------|--------------------------------------|
| Cable cross-section | Input IEC320-C20 / Output 8x IEC 320 |
| Mains protection | 10 A fuse |
| Auxiliary Mains protection | Not applicable |
| Common Input protection | Not applicable |
| >discr. Protection | |
| Noise (dBA) | 45 |
| Maximum Heat loss | 35 W |



Coromatic